

**Features:**

- Rotary speed, film carriage speed and the film tension can adjustable
- Automatic stretch film application & cutting is Pneumatically driven
- Equipped with Automatic height detection by photocell
- Machine is equipped with various durable top of the line components
- Equipped with Alarm and Emergency Button for Operators Safety
- PLC Controls the whole system with User Friendly Control Panel (HMI)
- Option for Powered IN/OUT feed Roller Conveyors. Rollers made of galvanized carbon steel to fit needed layout as per your demand.
- Option to include topfilm dispenser
- Options per project request.
- Option: Wrap heights 1800, 2400 or 2600mm, or per request.
- Option: Safety fence per layout 16onfiguration

SPECIFICATIONS

Packing Speed	40-50 pallets/hour
Film Aggregate	Single carriage motorized 250% pre stretch adjustable tension control
Rotation Speed	4-20 rpm (Adjustable)
Carriage Speed	6m/min (Adjustable)
Wrappign height default	500-2100mm with photocell for pallet height detection
Cutting of film	Heater cutting system
Conveyor height	500mm (can be customize)
Machine film LLDPE film :	LLDPE film, thickness 17-35micron, width 500mm, core \varnothing 76, max diameter \varnothing 250mm, weight 20kgs max
Air pressure	0.4-0.7 Mpa
Control system	PLC+HMI+ Frequency inverter
Voltage	3 Phase 5-line AC 380V 50Hz
STEP Item No.	43084000

- Equipped with Automatic height detection by photocell
- Machine is equipped with various durable top of the line components
- Equipped with Alarm and Emergency Button for Operators Safety
- PLC Controls the whole system with User Friendly Control Panel (HMI)
- Powered Roller Conveyor Line is made of galvanized carbon steel

SPECIFICATIONS

Packing Speed	50 pallets/hour
Top sheet cut method	Knife cutting
Top sheet pulling speed	12m/min
Top sheet size	W 1700mm, Length is adjustable
Conveyor height	500mm (can be customize)
PE film :	PE film, thickness 50-75microns, width1600-1700mm, net weight 120kgs max
Air pressure	0.4-0.7 Mpa
Control system	PLC+HMI+ Frequency inverter as per project
Voltage	3 Phase 5-line AC 380V 50Hz
STEP Item No. for Top Sheet Dispenser	43084100

